



STEAM POT With Digital Controller, Timer & Safety Cut-Out

Applications:

 Ideal for digestion of media in upto 2000 ml in Conical Flasks.

EQUITRON Advantages:

- · Water Level Indicating Device
- Safety thermostatic out-off (self resetting type) for assured low water detection - with visual indication.

Construction:

- · Fully stainless steel double walled construction with insulation of preventing
- Hinged lid with assisted lift for easy opening as well as effortless loading & removal of flasks.
- SS wiremesh heater cover for efficient steam movement and stable placement of media flasks
- Drain Valve for draining chamber water.
- Open port at top for venting of steam. Validation port provided as part of standard supply

- User settable Digital Temperature Controller with Timer





Model	Product	Internal Dimension L/B/Ht in mm	Heater	App. Shipping Details Net / Gr. / Volume
#8470-10	Steam Pot	600 x 400 x 350	3.0 kW	28 kg / 60 kg / 0.68 m³
#S3082-63	Stand for Steam Pot	620 ht	N.A.	-

All electrical appliances work on 230V AC, 50Hz, single phase. Other Voltages available on request.

Due to continuous improvement in dealors, the resolut supplied may have modified features.

MultiLab No.51/23, Arathoon Road, Off Appayu Lane. Royapuram, Chennai - 600 013, Tamil Nadu, India Ph:044-25984175, 45526026, 094441 62346 Email: multilabindia@gmail.com, www.multilab.biz