

AC CURRENT CONTROLLER/MONITOR

Model : PAA-6069

ISO-9001, CE, IEC1010



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

The Art of Measurement

AC Current CONTROLLER/MONITOR

Model : PAA-6069

FEATURES

* Professional ACA meter with standard DIN case (96 x 48 mm) and Control/Alarm function.
* Microprocessor circuit ensures high accuracy and provide special functions and features.
* Large red LED display, high brightness and easy to read.
* Input signal (without CT) : ACA : 0.05 to 10.00 ACA, 40 to 400 Hz.
* True rms for ACA measurement.
* ACA input can cooperate the external CT (Current transformer) to expand the measurement range. The CT range can be adjusted with default.
* Control setting, Hi/Lo alarm setting.
* Control relay output, alarm relay output.
* Control Relay will make action when the reading value reach to control value.
* Alarm Relay will make action when the reading value reach to high/low alarm value.
* Hysteresis value setting for control and alarm function.
* Power : 90 ACV to 264 ACV, 50/60 Hz.
* RS232/USB computer interface.
* Option data acquisition software.

GENERAL SPECIFICATIONS

Display	Large LED display. 4 digit LED . 14 mm (0.55 inch) digit height . 5 indicators . PV (process value) indicator SV (set value) indicator Control out indicator Alarm out indicator A (ACA) indicator	
Circuit	Custom chip of microprocessor LSI circuit.	
ACA measurement	0.05 ACA to 10.00 ACA. * <i>True rms value</i>	
Sampling Time	Approx. 0.8 second.	
Relay Output	Number	2 relays
	Function	<i>Relay 1 :</i> Control relay. <i>Relay 2 :</i> High/Low alarm relay.
	Max load	0.5 ACA/250 ACV 0.5 DCA/24 DCV * Do not apply the relay contact load current > 0.5 A, other wise the relay may be damaged permanently without warranty.
Setting Function	<i>1st layer setting procedures</i>	CtLo (Control low limit) CtHi (Control high limit) ALLo (Alarm low limit) ALHi (Alarm high limit)
	<i>Second layer setting procedures</i>	CtSt (CT rate setting) CtHy (Control hysteresis value setting) ALHy (Alarm hysteresis value setting)

Over input	" - - - " mark indication.
Zero Adjustment	Automatic adjustment.
Data Output	RS232 / USB PC Computer interface. * Connect the optional RS232 cable , UPCB - 02 will get the RS232 plug. * Connect the optional USB cable, USB - 01 will get the USB plug.
Operating Temperature	0 to 50 °C .
Operating Humidity	Less than 80% R.H.
Power Supply	90 to 260 ACV, 50/60 Hz.
Power Consumption	Approx. 3.3 VA/AC 110V. Approx. 4.9 VA/AC 220V. * <i>Under no load</i>
Weight	261 g/ 0.57 LB.
Dimension	DIN size : 96 x 48 mm. Panel cut size : 92 x 46 mm. Depth : 110 mm.
Accessories Included	Instruction manual..... 1 PC Case holder with screw..... 2 PCs
Optional Accessories	USB cable , USB - 01 RS232 cable , UPCB - 02 Data Acquisition software SW-U801-WIN * Real time SD card datalogger DL-9602SD * GSM controller, GSM-889. * Interface cable (cable between meter to GSM-889) , GMCB-89.

ELECTRICAL SPECIFICATIONS

Direct input (without CT)

Range	0.05 ACA to 10.00 ACA
Resolution	0.01 ACA
Accuracy	± (0.5 % + 5d) reading
Remark :	* T16, T15 ACA input : 0.05 ACA to 10.00 ACA. * Accuracy is test under input signal is sine wave, 50/60 Hz. * ACA frequency response is from 40 to 400 Hz. * ACA measurement is True RMS value. * Accuracy value is specified within 23°C ± 5°C

With CT (Current transformer)

Range	1 ACA to 2000 ACA
Resolution	1 ACA
Accuracy	± (0.5 % + 5d) reading
Remark :	* Measuring Signal come from the rear terminals . * T16, T15 ACA input : 0.05 ACA to 10.00 ACA. CT (Current transformer) adjust value : x 1 to x 200. * Accuracy is test under input signal is sine wave, 50/60 Hz. * Accuracy is specified for the meter only, not include the accuracy of CT (Current transformer) .

* Appearance and specifications listed in this brochure are subject to change without notice.