

SOUND ADAPTER

Model : SL-417

ISO-9001, CE, IEC1010



FEATURES

- * Cooperate with the Environment Meter EM-9300SD, EM-9200, EM-9100 as a professional sound level meter.
- * 30 to 130 dB, 3 ranges.
- * Frequency weighting networks are designed to meet the IEC 61672 class 2.
- * A weighting networks are conformity to standards.
- * Fast Time weighting dynamic characteristic modes.
- * Condenser microphone for high accuracy & long-term stability.
- * Over/Under indicator.
- * Low battery indicator.
- * Electric condenser microphone.
- * Size of microphone : 1/2 inch standard size.



LUTRON ELECTRONIC

The Art of Measurement

SOUND ADAPTER

Model : SL-417

ISO-9001, CE, IEC1010



FEATURES

- * Cooperate with the Environment Meter EM-9300SD, EM-9200, EM-9100 as a professional sound level meter.
- * 30 to 130 dB, 3 ranges.
- * Frequency weighting networks are designed to meet the IEC 61672 class 2.
- * A weighting networks are conformity to standards.
- * Fast Time weighting dynamic characteristic modes.
- * Condenser microphone for high accuracy & long-term stability.
- * Over/Under indicator.
- * Low battery indicator.
- * Electric condenser microphone.
- * Size of microphone : 1/2 inch standard size.



LUTRON ELECTRONIC

The Art of Measurement

SOUND LEVEL ADAPTER

Model : SL-417

FEATURES	
* Cooperate with the ENVIRONMENT METER, EM-9300SD, EM-9200, EM-9100 to be as a professional sound level meter.	
* 30 to 130 dB, 3 ranges.	
* Frequency weighting networks are designed to meet the IEC 61672 class 2.	
* A weighting networks are conformity to standards.	
* Fast Time weighting dynamic characteristic modes.	
* Condenser microphone for high accuracy & long-term stability.	
* Over/Under range indicator.	
* Low battery indicator.	

SPECIFICATIONS	
Measurement Range	30 to 130 dB, 3 ranges Range 1 : 30 to 80 dB. Range 2 : 50 to 100 dB. Range 3 : 80 to 130 dB.
Output	10 mV per 1 dB.
Accuracy ($23 \pm 5^{\circ}\text{C}$)	Frequency weighting meet IEC 61672 class 2, calibrating input signal on 94 dB (31.5 Hz to 8 kHz), then the accuracy of A frequency weighting is specified as following : <i>31.5 Hz - ± 3.5 dB, 63 Hz - ± 2.5 dB, 125 Hz - ± 2.0 dB 250 Hz - ± 1.9 dB, 500 Hz - ± 1.9 dB, 1 kHz - ± 1.4 dB 2 kHz - ± 2.6 dB, 4 kHz - ± 3.6 dB, 8 kHz - ± 5.6 dB</i>
Frequency Weighting Network	Characteristics of A weighting. A weighting : The characteristic is simulated as " Human Ear Listing " response.
Frequency	31.5 Hz to 8,000 Hz.
Calibrator	B & K (Brueel & Kjaer) : Multi-fuction acoustic calibrator, Model : 4226.
Microphone type	Electric condenser microphone.
Size of microphone	1/2 inch standard size.
Calibration VR	Build in external calibration VR.
Battery	DC 9 V battery (006P, 6F22). @ <i>Alkaline or heavy duty type.</i>
Power Consumption	Approx. DC 12 mA.
Operating Temperature	0 to 50 $^{\circ}\text{C}$ (32 to 122 $^{\circ}\text{F}$).
Operating Humidity	Less than 80% RH.
Weight	220 g/0.49 LB (including battery).
Dimension	<i>Main instrument</i> : 107 x 53 x 29 mm (4.2 x 2.1 x 1.1 inch).
	<i>Probe</i> : Dia. 12.7 mm x 58 mm (Dia. 0.5 inch x 2.28 inch).
Accessories Included	Operation Manual..... 1 PC.
Optional Calibrator, Accessory	94 dB Sound Calibrator, Model : SC-941. 94/114 dB Sound Calibrator, Model : SC-942. Wind shield ball, Model : SB-01

* Appearance and specifications listed in this brochure are subject to change without notice.

1109-SL417