

Reveal ShieldPRO

Handheld thermal camera designed
for law enforcement



Reveal ShieldPRO

- 320 x 240 Thermal sensor
- ▼ 24° Field of view
- 📍 Long range detection
- 💧 IP67 rating
- 🌙☀️ Works day & night
- 🔦 300 lumen LED flashlight

Highly durable and easy to use, RevealShieldPRO combines a high-performance 320 x 240 thermal sensor with intuitive user interface. When you need it, a powerful 300-lumen LED light is available at the touch of a button. RevealShieldPRO was specifically designed for Law Enforcement Professionals. Built with a rugged over-mold housing and IP67 rating, RevealShieldPRO is fit to withstand the elements. Thermal Imaging helps you safeguard land and borders, quickly clear a room, find discarded evidence at night, and track perpetrators without a flashlight giving your position away. Even the most elusive suspects can't hide their heat signature.

Features

320 x 240 thermal sensor

Excellent image clarity and sensitivity with 76,800 pixels

Long-range detection

Detect a human at long distances in complete darkness

3.5 hour runtime

Long-Lasting rechargeable battery

Durable design

Designed for the outdoors with IP67 rating

Lightweight & easy-to-use

Intuitive, 3 button controls provide easy operation of your camera

Benefits

Safeguard buildings, land, and borders

Tactical surveillance technology that's affordable

Better than night vision

Even the most elusive perpetrators can't hide their heat signature

Personal safety

Clear a room without putting yourself in harm's way

Situational awareness

It's a lot easier to stay safe when you can see in the dark

Recover evidence

Recover discarded or hidden evidence invisible to the human eye

Technical Specifications

Thermal sensor	: 320 x 240
Detection distance	: 758 meters
Recognize distance	: 190 meters
Identify distance	: 108 meters
Field of View	: 24 Degree FOV
Frame rate	: 9 Hz or >15 Hz
Zoom	: 4x digital zoom
IP rating	: IP67 Waterproof
Display	: Gorilla® glass Uncooled
Microbolometer	: Vanadium oxide
Startup time	: 2-3 seconds
Spectral range	: 7.5-14 microns
User interface	: Self-contained device with 3 button navigation
Storage temp.	: -40°F to 140°F (-40°C to 60°C)
Operating Temp.	: -40°F to 120°F (-20°C to 50°C)
Run time	: Up to 3.5 hours thermal imaging
Battery	: Rechargeable lithium battery
Product details	: Product dimension: 122mm x 60mm x 30mm product weight: 180g 4 lbs
Box details	: Box dimension: 230mm x 185mm 185mm x 61mm Box weight: 660g .145 lbs

